

December/2018 100% Real Exam Questions-Braindump2go 300-360 VCE and 300-360 PDF Dumps 185Q Download[Q107-Q117

December/2018 Braindump2go 300-360 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-360 Real Exam Questions:1.|2018 Latest 300-360 Exam Dumps (PDF & VCE) 185Q
Download:<https://www.braindump2go.com/300-360.html>2.|2018 Latest 300-360 Exam Questions & Answers
Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNaFhjTjl4Uk0tbDg?usp=sharing>**QUESTION 107**Which three network located in a warehouse? (Choose three.)A. conveyor beltsB. employee schedulesC. ceiling heightD. variable inventory quantitiesE. types of wallsF. deliveries**Answer: BCE****QUESTION 108**During a post-deployment survey, the wireless engineer notices that offices in surrounding suites also have wireless networks and the 2.4 Ghz band is highly utilized Which configuration must the engineer make on the wireless network using this new information?A. Disable 802.11 b/g data rates.B. Enable Band Sect in the WLCC. Disable RRM in the WLC.D. Enable rogue access point containment.**Answer: D****Explanation:** Monitoring Rogue Access Point AlarmsRogue access point radios are unauthorized access points detected by one or more Cisco lightweight access points. This page displays rogue access point alarms based on the severity you clicked in the Alarm Monitor.
https://www.cisco.com/c/en/us/td/docs/wireless/mse/3350/5-2/wIPS/configuration/guide/msecg_wIPS/msecg_appB_wIPS.html#wp1244525**QUESTION 109**An engineer must design a wireless voice network and is auditing the existing configuration.Which two actions must be taken? (Choose two.)A. Enable Platinum QoS profile on the SSIDB. Disable Coverage Hole Detection.C. Ensure the switch ports trust DSCP QoS markingsD. Disable WMM on the QoS tabE. Ensure that Client Load Balancing is enabled.**Answer: AC****Explanation:**<https://mrnciew.com/2012/11/28/understanding-wireless-qos-part-1/>**QUESTION 110**An engineer is implementing QoS for a new wireless voice network. Which two considerations should be identified first? (Choose two.)A. QoS markingB. policingC. QoS requirementsD. data traffic usageE. traffic classification**Answer: CE****QUESTION 111**An engineer is determining powering requirements for a P2P wireless link using Cisco Aironet 1572EC access points.Which power method is valid for the access point?A. 802.3af Power over EthernetB. Power over CableC. Cisco Inline PowerD. 802.3at Power over Ethernet**Answer: B****QUESTION 112**17.A network engineer is performing a site survey in preparation for an installation. Which three hardware parameters must be inspected? (Choose three.)A. routing protocol usedB. PoE capabilityC. switch STP capabilityD. distance of antenna to communications roomE. switch port availabilityF. distance of access point to communications room**Answer: BEF****QUESTION 113**An engineer has added an access point to a deployment after a post-installation site survey. The engineer then notices that there has been an increase in co-channel interference and retransmissions. Which two features can help mitigate the issue? (Choose two.)A. Coverage Hole DetectionB. Transmit Power ControlC. Enhanced Distributed Channel AccessD. Cisco Compatible ExtensionsE. Dynamic Channel Assignment**Answer: CE****QUESTION 114**You are planning the coverage for wireless VoIP by using Ekahau. Which signal strength does Ekahau recommend using for VoIP?A. -84 dBmB. -76 dBmC. -67 dBmD. -53 dBm**Answer: C****Explanation:**Each vendor has their own recommended signal strength for a given data rate or application. For instance, one vendor may recommend designing their VoIP solution at -67 dBm (perhaps the most widely-used value for VoIP deployment if I had to choose one), while another may say -70 dBm. In most cases the values will differ only by a couple dB.
<https://www.ekahau.com/blog/2015/01/13/ekahau-site-survey-heatmap-visualizations-part-2-signal-stren-gth/>**QUESTION 115**You must upgrade a data-based wireless network to support Voice over Wireless. Which RSSI measurement do you use to redesign the wireless network?A. -65 dBmB. -72 dBmC. -75 dBmD. -67 dBm**Answer: D****QUESTION 116**You must create a simple implementation of QoS on a WIAN. The implementation must allow clients to prioritize traffic into these four classes:- voice- video- best effort- backgroundWhich option do you enable?A. NBAR2B. NetFlow v9C. WMMD. Cisco AVC**Answer: C****Explanation:**WMM ClassificationWMM uses the 802.1P classification scheme (part of the IEEE 802.1D MAC Bridges standard). This classification scheme has eight priorities that WMM maps to four access categories with WMM designations: AC_BK--BackgroundAC_BE--Best effortAC_VI--VideoAC_VO--Voice
https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-1/Enterprise-Mobility-8-1-Design-Guide/Enterprise_Mobility_8-1_Deployment_Guide/ch5_QoS.html**QUESTION 117**A post-deployment active wireless site survey was just completed for a company. Which two pieces of information must be included in the site survey report? (Choose two.)A. client performance metrics obtained during the surveyB. heat maps from the data that was capturedC. floor plans for Cisco Prime InfrastructureD. existing WLC configurationsE. RRM recommendations for the WLC**Answer: BDE****Explanation:**
<https://www.cisco.com/c/en/us/support/docs/wireless/5500-series-wireless-controllers/116057-site-survey-guidelines-wlan-00.html#anc28>**!!!RECOMMEND!!!**1.|2018 Latest 300-360 Exam Dumps (PDF & VCE) 185Q

Download:<https://www.braindump2go.com/300-360.html2>,|2018 Latest 300-360 Study Guide Video: YouTube Video:
[YouTube.com/watch?v=1MSGk2z6Rd8](https://www.youtube.com/watch?v=1MSGk2z6Rd8)